



# FIRM-FILL® SCM-750



## Product Description

FIRM-FILL® SCM-750 is designed for use in renovation projects and other challenging noise control environments. It is an entangled net polypropylene sound control mat engineered to limit impact sound transmission in the most challenging floor-ceiling assemblies. It's 3/4" (19 mm) core provides the greatest isolation on the market.

FIRM-FILL® SCM-750 is color-coded green to ensure choosing the proper thickness for installation. It is designed for use with FIRM-FILL® Brand Gypsum Underlayments to provide a complete fire and sound control system.

### TECHNICAL DATA

### PROPERTIES

|                          |                                                |
|--------------------------|------------------------------------------------|
| Core Thickness (Nominal) | 3/4" (19 mm) (Minimum Gypsum Thickness 1 1/2") |
| Width                    | 60" (152.4 cm)                                 |
| Coverage per Roll        | 200 ft² (18.5 m²)                              |
| Roll Weight              | 28 lbs (12 kg)                                 |
| Steiner Tunnel           | Class A                                        |

## Related Products

FIRM-FILL® SCM-750 should be specified to use in conjunction with FIRM-FILL® Gypsum Underlayments. Hacker Industries, Inc. also supplies Hacker Reinforcement, FIRM-FILL® SCM Tape, Hacker Floor Sealer, Hacker Perimeter Isolation, and Hacker TopCoat® SP (Surface Prep). For more products, visit [hackerindustries.com/products.shtml](https://hackerindustries.com/products.shtml).

## Compliance

- ICC-ESL-1452
- ICC-ESR-3386
- HUD 1255

## Installation



**1** Isolation strips are installed, then taped, around the perimeter of the whole room and around any vertical penetrations of the floor.



**2** Lay down sound mat over the entire subfloor, colored side down.



**3** Seams between sound mat rolls are adhered with tape.



**4** Sound mat is topped with a Hacker Underlayment. For depth, please refer to Hacker Industries, Inc.'s *Thickness Guidelines*.



**5** Finished floor coverings can be installed when the gypsum concrete is completely dry.

# FIRM-FILL® SCM-750



Class A fire rated product;  
Code Compliant; over 130  
UL Listings



Ideal for challenging floor/  
ceiling assemblies and  
renovation projects



Lightweight and easy  
to install correctly



Cost-effective way to address  
noise concerns and improve  
IIC ratings



Minimal deflection, no creep  
or long-term degradation



Installed only by our trained  
Licensed Applicators across  
North America

## Sound Testing & UL Fire Rated Designs

| UL FIRE RATED DESIGNS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| L003, L006, L201, L202, L206, L208, L209, L210, L211, L212, L501, L502, L503, L504, L505, L506, L507, L508, L509, L510, L511, L512, L513, L514, L515, L516, L517, L518, L519, L520, L521, L522, L523, L524, L525, L526, L527, L528, L529, L530, L532, L533, L534, L535, L536, L537, L538, L539, L540, L541, L542, L543, L545, L546, L547, L549, L550, L551, L556, L557, L558, L560, L562, L563, L564, L569, L570, L574, L576, L577, L579, L581, L583, L585, L587, L588, L589, L590, L592, L593, L598 |
| M500, M501, M502, M503, M504, M505, M506, M508, M509, M510, M511, M513, M514, M515, M517, M519, M520, M521, M530, M531, M538, M540, M544, M545, M546, M550, M553, M562                                                                                                                                                                                                                                                                                                                               |
| G230, G516, G524, G553, G561, G565, G566, G587, G594, G595                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| H502, H516                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| J917, J919, J920, J924, J927, J931, J957, J991, J994                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

Published acoustic and fire systems tests were conducted under controlled laboratory or field conditions and reflect results applicable only to those specific assemblies. For more information on acoustical assemblies, visit <https://hackerindustries.com/pdfs/hacker-industries-acoustical-design-guide.pdf>.

## Limitations

1. Do not use in exterior locations or below-grade.
2. Shall not be used without a FIRM-FILL® Gypsum Concrete Underlayment.
3. Do not install where continuous exposure to moisture is a possibility.
4. Structure shall be designed so that deflection does not exceed L/360 live or dead load. Certain floor coverings such as marble, limestone, travertine, and wood may have more restrictive deflection limits. Consult the appropriate floor covering manufacturer for recommendations.
5. FIRM-FILL® SCM-750 shall be installed with a perimeter isolation strip.
6. Do not use mechanical fasteners to install FIRM-FILL® SCM-750, as mechanical fasteners conduct impact sound, reducing acoustical isolation.
7. FIRM-FILL® SCM-750 is but one component of an effective sound and fire-control system. Care must be taken in the installation of all components to assure the ultimate design performance.

## WARNING

Laboratory tests are not a guarantee of field performance because of the issues noted above and many other design errors that may occur. Please consult a professional acoustical consultant to assure plans are proper and that the floor/ceiling assembly can perform to expectations.

## NOTES

The information in this document is subject to change without notice. Hacker Industries, Inc., and/or its affiliates assume no responsibility for any errors that may inadvertently appear in this document. Consult Hacker Industries, Inc., for updated information.

## WARRANTY

HACKER INDUSTRIES, INC. SHALL NOT BE LIABLE FOR INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES, DIRECTLY OR INDIRECTLY SUSTAINED, NOR FOR ANY LOSS CAUSED BY APPLICATION OF THESE GOODS NOT IN ACCORDANCE WITH CURRENT PRINTED INSTRUCTIONS OR FOR OTHER THAN THE INTENDED USE. OUR LIABILITY IS EXPRESSLY LIMITED TO REPLACEMENT OF DEFECTIVE GOODS. ANY CLAIMS SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN 30 DAYS FROM THE DATE IT WAS DISCOVERED. EXTENDED WARRANTY IS AVAILABLE ON THE HACKER INDUSTRIES, INC. WEBSITE.

## TRADEMARKS

FIRM-FILL®, Let Our Products Floor You® and the associated logos are trademarks of Hacker Industries, Inc.

